



THE **12**
PASSIVE
ON WALL



Speaker type	Time coherent 12" coax point-source
Passive Active	Passive
Enclosure type	Vented
SPL	Calculated data 123 dB cont. / 126 dB peak
Frequency Range	Calculated data 80 Hz - 20 kHz
Sensitivity	98 dB / 1W/m
Power handling	600 W
Impedance	8 Ω
Woofer	12" woofer featuring lightweight paper cone and high-power long throw magnet system
Tweeter Hochtöner	1", soft dome, 44mm voice coil
Directivity horizontal x vertical in Deg°	85° x 85°
Input Terminal	One 4-conductor Phoenix 12 AWG (3.3 mm ²) push on binding post
Enclosure Gehäuse	MDF

Width	15.35" 390 mm
Height	24.21" 615 mm
Depth with plug	6.89" 175 mm
Depth with grille	7.24" 184 mm
Depth grille	0.35" 9 mm
Weight	47.4 lbs 22.0 kg
Finish	Black matte
Custom colour options	Piano lacquer: colour of choice, matt or other finishes upon request, color of choice
Shape customization	Upon request Auf Anfrage
Mounting	4 x wall brackets for horizontal and vertical installation + VESA 200 x 100 mounting points

All speakers are supplied with a front cover as standard |
Alle Lautsprecher werden mit Abdeckung ausgeliefert



Technical modifications subject to change without further notice | Technische Änderungen vorbehalten