

Preference



decorum series

NEW Frameless Design with Magnetically-Attached Grille

K-6LCRSd In-Ceiling 15° Angled LCRS

Specifications:

- 6-1/2" Round **Frameless**
- Frequency Response: 45Hz - 21kHz \pm 3 dB
- Power Handling: 50 watts nom. 100 max.
- Sensitivity: 86dB 1 watt / 1 meter
- Tweeter: 1" Teton® soft dome pivoting
- Impedance: 8 ohms nominal

Features:

- Woven woofers made from genuine DuPont™ Kevlar®
- Baffle mounted mid & high frequency acoustic compensation / EQ switches
- Magnetic, frameless, vibration-free, all-weather grille
- High temperature Polyimide voice coils
- High-excursion linear motor design
- Polyswitch overdrive protection
- Augmented dispersion design
- Sold and shipped individually
- Proven mounting system
- High-grade crossovers

Dimensions:

- Overall Dimension: 9-7/8" diameter
- Cut-Out: 8-5/8" diameter x 5" deep



Optional Pre-Construction Bracket & Vapor Dome



Optional Square Frameless Grille

MGS-8f



DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



Rev. E

Preference®

(775) 355-0405 + Fax: (775) 355-0646
www.preference-audio.com + info@preference-audio.com

View the entire
Preference
Product Line:

