

decorum series

NEW Frameless Design with Magnetically-Attached Grille

K-62d Single Point Stereo 6-1/2" 2-way In-Ceiling / Wall Loudspeaker


Frequency Response: 55Hz - 21kHz ± 3 dB Power Handling: 55 watts nom. 110 max. Sensitivity: 91dB 1 watt / 1 meter Impedance: 8 ohms nominal Tweeter: 3/4" Tetoron® soft dome tweeters Cut-Out Dimensions: 7-1/4" dia.x 3-5/16" deep Overall Dimensions: 8-7/16" diameter Sold and shipped individually

K-82d Single Point Stereo

Frequency Response: 35Hz - 21kHz ± 3 dB Power Handling: 60 watts nom. 120 max. Sensitivity: 91dB 1 watt / 1 meter Impedance: 8 ohms nominal Tweeter: 3/4" Tetoron® soft dome tweeters Cut-Out Dimensions: 8-5/8" dia.x 3-7/8" deep Overall Dimensions: 9-7/8" diameter Sold and shipped individually

Features:

- · High-grade crossovers with polyswitch overdrive protection
- Magnetic, frameless, vibration-free, all-weather grille .
- Woven woofers made from genuine DuPont[™] Kevlar® .
- Dual high temperature Polyimide voice coils



DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.





Optional Square Frameless Grilles MGS-6f for MGS-8f for K-82d K-62d





(775) 355-0405 + Fax: (775) 355-0646 www.preference-audio.com + info@preference-audio.com



