

Comparison Chart: Headphone Preamplifier

	Model	<i>Phonitor xe</i>	<i>Phonitor x</i>	<i>Phonitor se</i>
Phonitor Matrix	Crossfeed values	6	6	2
	Speaker angles	4	4	1
Remote control	Volume	●	●	○
Laterality control	Super fine balance	●	●	○
Stereo/Mono	Playback mode	●	●	○
VU meters	∅ 36 mm illumin. VUs	●	●	○
	0 dBVU calibrated (+ 4 dBu)	0 / 6 / 12 dB	0 / 10 dB	○
Headphone output	4-pin XLR (balanced)	●	●	○
	1/4" Jack	●	●	●
	Front & rear outputs	●	○	○
	Additional output boost	+22 dB	+12 / +22 dB	+12 dB
Line output	XLR (balanced)	○	●	○
	RCA (unbalanced)	○	●	○
	Speaker output	○	●	○
Line input	XLR (balanced)	●	●	○
	RCA (unbalanced)	●	●	●
	RCA -10 dBV to 0 dBu boost	●	○	○
DA Converter (optional)	Model	DAC768	DAC768xs	DAC768xs
	DLP120	●	○	○
	Bit/max SR kHz	32 / 768	32 / 768	32 / 768
	DSD	256fs	256fs	256fs
	USB	●	●	●
	AES	●	○	○
	Coaxial	●	●	●
	Optical	●	●	●
Housing	Dimensions	278 x 100 x 300 mm 11" x 4" x 11,81"	278 x 100 x 300 mm 11" x 4" x 11,81"	278 x 57 x 300 mm 11" x 2,9" x 11,81"
	W x H x D (feet incl.)	4.9 kg / 10.8 lbs	4.4 kg / 9.7 lbs	2,8 kg / 6.17 lbs